PRESSURE SWITCH EXPLOSION PROOF TYPE

PS2000M

CLASS I, GROUPS A, B, C, D; CLASS II, GROUPS E, F, G; NEMA 4X

Protection: IP68

Proof Pressure to 5000psi Adjustable Ranges: 10~4000psi Temperature: -30 to 205°C


The New-Flow PS2000X, an explosion proof pressure switch, is designed to be used in control systems. PS2000X has high set point repeatability and narrow dead band features. A variety of range selections are available upon request. Easily adjusted to the set point, and no special tools needed!

Technical Data

Switch Data: one SPDT & two SPDT Microswitch, 15amps 125/250VAC, DC 125V 0.4A, DC 30V 3A / Gold Contact Microswitch 1A 125/250VAC Housing: die cast aluminum alloy with paint Conduit Connection: ¾" or ½"NPT Female Pressure Element: welded type diaphragm Process Material: wetted parts all in SS316 Process Connection: ½" or ¼" NPT Female

Repeatability: ±1% of full scale

PS2000X Pressure Switch Explosion Proof Type CERT Mark & S. CRUTE MARK (I. N. NEW A) REMARK & S. CRUTE MARK (I. N. NEW A) REMARK (I. N. NEW A) REMARK



The picture and dimensions is for Explosion type A (Certificate on Housing only). Type B & C (EC-type) is on request.

Range Selection Table

Code	Adjustable Range	Dead Band	Maximum Pressure Proof			
10R	10~100psi	0.9~2.1	3000psi 3000psi			
20R	35~200psi	1.4~5.4				
30R	50~300psi	1.4~6.9	3000psi			
60R	100~600psi	1.7~15.1	3000psi			

	Code	Adjustable Range	Dead Band	Maximum Pressure Proof
	130R	100~1300psi	5.5~15	3000psi
	240R	300~2400psi	19.6~39.5	4000psi
	400R	400~4000psi	32.5~65.6	5000psi
1				

Ordering Information

Urdering Information											
PS2000X	PS2000X Code Range										
	10R 10~100 psi 20R 35~200			35~200 p	osi	30R 50~300 psi 60R		60R	100~600 psi		
130R 100~1300			0 psi	240R 300~2400		0 psi	400R 400~4000 psi				
Code Wetted Parts Material				erial	al						
		Α	SS316								
			Code	Process Connection							
				(1) ½"N	PT Female	(2) ¼"NI	PT Female)			
Code Conduit Connection											
				(E) ¾"NPT Female, standard (F) ½"NPT Female							
					Code Switch Form						
				1		One SPDT	7 2 Two SPDT (one setting point) 3 Gold		Gold Contact (SPDT)		
						Code	Explosi	on Type			
						A	A Certificate on Housing Only: Class I, Groups A, B, C, D; Class II, Gruops E, F, G; NEMA 4X				
					B EC-Type Examination: ITRI/TAIWAN- Exd IIB + H ₂ T6						
						C EC-Type Examination: ATEX- II 2 G D Ex db IIB + H ₂ T6 Gb Ex tb IIIC T85°C Db					
						D IECEx Certificate on Housing Only: Ex d IIB + H2 Gb T6 Ex tb IIIC Db T85°C					
V	V	+	\	V	+	+					
PS2000X							Comple	te Ordering Code			